

Item Catalogue

NUPCO CODE: 4232150026400 | SN: 358

NUPCO ITEM DESCRIPTION

SCREW, CANNULATED PARTIAL THREADED SELF-DRILLING 4.5MM TITANIUM ASSORTED TYPES AND LENGTHS AS REQUESTED BY END USER

VENDOR PRODUCT DESCRIPTION

OsteoMed ExtremiFix Midsize 4.5 mm headed cannulated screws, short/long thread

SKU CODES INCLUDED FOR THIS NUPCO CODE

- 319-4520
- 319-4522
- 319-4524
- 319-4526
- 319-4528
- 319-4530
- 319-4532
- 319-4534
- 319-4536
- 319-4538
- 319-4540
- 319-4542
- 319-4544
- 319-4546
- 319-4548
- 319-4550
- 319-4555
- 319-4560
- 319-4565
- 319-4570
- 319-4541
- 319-4543
- 319-4545
- 319-4547
- 319-4549
- 319-4551
- 319-4556
- 319-4561
- 319-4566
- 319-4571

Indications

The OsteoMed ExtremiFix Midsize I Large Cannulated Screw system is indicated for use in bone reconstruction, osteotomy, arthrodesis, and fracture fixation of foot, ankle, and long bones (upper and lower extremity).

Contraindications

Use of the OsteoMed ExtremiFix Midsize I Large Cannulated Screw system is contraindicated in cases of active or suspected infection or in patients who are immunocompromised; in patients previously sensitized to titanium; or in patients with certain metabolic diseases. It is further contraindicated in patients exhibiting disorders which would cause the patient to ignore the physician's pre- and/or post-operative instructions and/or the limitations of internal rigid fixation implants.

Warnings

1. Re-operation to remove or replace implants may be required at any time due to medical reasons or device failure. If corrective action is not taken, complications may occur.
2. Use of an undersized screw in areas of high functional stresses may lead to implant fracture and failure.
3. Plates and screws, wires, or other appliances of dissimilar metals should not be used together in or near the implant site.
4. Instruments, guide wires, and screws are to be treated as sharps.
5. It is recommended to remove any fractured implants and/or instruments from patients during surgery. If unable to remove, notify patient.
6. Use of screws in high density bone may result in implant and/or instrument fracture or failure upon insertion.
7. The OSTEOMED ExtremiFix Midsize & Large Cannulated Screw system is recommended for use in patients with sufficient bone quality to sustain effectiveness and benefits of rigid fixation.
8. The user should be aware of possible allergic reactions to materials used in the device. The patient should be informed on this matter by the user.
9. Failure to follow instructions may result in device not operating as intended.
10. Failure to follow sterilization parameters may result in device not operating as intended.

Ordering Information

Midsize Implants



4.5 mm Headless Short Thread Screws

317-4520	4.5 x 20 mm Cannulated Headless Compression Screw, Short Thread
317-4522	4.5 x 22 mm Cannulated Headless Compression Screw, Short Thread
317-4524	4.5 x 24 mm Cannulated Headless Compression Screw, Short Thread
317-4526	4.5 x 26 mm Cannulated Headless Compression Screw, Short Thread
317-4528	4.5 x 28 mm Cannulated Headless Compression Screw, Short Thread
317-4530	4.5 x 30 mm Cannulated Headless Compression Screw, Short Thread
317-4532	4.5 x 32 mm Cannulated Headless Compression Screw, Short Thread
317-4534	4.5 x 34 mm Cannulated Headless Compression Screw, Short Thread
317-4536	4.5 x 36 mm Cannulated Headless Compression Screw, Short Thread
317-4538	4.5 x 38 mm Cannulated Headless Compression Screw, Short Thread
317-4540	4.5 x 40 mm Cannulated Headless Compression Screw, Short Thread
317-4542	4.5 x 42 mm Cannulated Headless Compression Screw, Short Thread
317-4544	4.5 x 44 mm Cannulated Headless Compression Screw, Short Thread
317-4546	4.5 x 46 mm Cannulated Headless Compression Screw, Short Thread
317-4548	4.5 x 48 mm Cannulated Headless Compression Screw, Short Thread
317-4550	4.5 x 50 mm Cannulated Headless Compression Screw, Short Thread
317-4555	4.5 x 55 mm Cannulated Headless Compression Screw, Short Thread
317-4560	4.5 x 60 mm Cannulated Headless Compression Screw, Short Thread
317-4565	4.5 x 65 mm Cannulated Headless Compression Screw, Short Thread
317-4570	4.5 x 70 mm Cannulated Headless Compression Screw, Short Thread



4.5 mm Headless Long Thread Screws

317-4541	4.5 x 40 mm Cannulated Headless Compression Screw, Long Thread
317-4543	4.5 x 42 mm Cannulated Headless Compression Screw, Long Thread
317-4545	4.5 x 44 mm Cannulated Headless Compression Screw, Long Thread
317-4547	4.5 x 46 mm Cannulated Headless Compression Screw, Long Thread
317-4549	4.5 x 48 mm Cannulated Headless Compression Screw, Long Thread
317-4551	4.5 x 50 mm Cannulated Headless Compression Screw, Long Thread
317-4556	4.5 x 55 mm Cannulated Headless Compression Screw, Long Thread
317-4561	4.5 x 60 mm Cannulated Headless Compression Screw, Long Thread
317-4566	4.5 x 65 mm Cannulated Headless Compression Screw, Long Thread
317-4571	4.5 x 70 mm Cannulated Headless Compression Screw, Long Thread



4.5 mm Headed Short Thread Screws

319-4520	4.5 x 20 mm Cannulated Headed Screw, Short Thread
319-4522	4.5 x 22 mm Cannulated Headed Screw, Short Thread
319-4524	4.5 x 24 mm Cannulated Headed Screw, Short Thread
319-4526	4.5 x 26 mm Cannulated Headed Screw, Short Thread
319-4528	4.5 x 28 mm Cannulated Headed Screw, Short Thread
319-4530	4.5 x 30 mm Cannulated Headed Screw, Short Thread
319-4532	4.5 x 32 mm Cannulated Headed Screw, Short Thread
319-4534	4.5 x 34 mm Cannulated Headed Screw, Short Thread
319-4536	4.5 x 36 mm Cannulated Headed Screw, Short Thread
319-4538	4.5 x 38 mm Cannulated Headed Screw, Short Thread
319-4540	4.5 x 40 mm Cannulated Headed Screw, Short Thread
319-4542	4.5 x 42 mm Cannulated Headed Screw, Short Thread
319-4544	4.5 x 44 mm Cannulated Headed Screw, Short Thread
319-4546	4.5 x 46 mm Cannulated Headed Screw, Short Thread
319-4548	4.5 x 48 mm Cannulated Headed Screw, Short Thread
319-4550	4.5 x 50 mm Cannulated Headed Screw, Short Thread
319-4555	4.5 x 55 mm Cannulated Headed Screw, Short Thread
319-4560	4.5 x 60 mm Cannulated Headed Screw, Short Thread
319-4565	4.5 x 65 mm Cannulated Headed Screw, Short Thread
319-4570	4.5 x 70 mm Cannulated Headed Screw, Short Thread



4.5 mm Headed Long Thread Screws

319-4541	4.5 x 40 mm Cannulated Headed Screw, Long Thread
319-4543	4.5 x 42 mm Cannulated Headed Screw, Long Thread
319-4545	4.5 x 44 mm Cannulated Headed Screw, Long Thread
319-4547	4.5 x 46 mm Cannulated Headed Screw, Long Thread
319-4549	4.5 x 48 mm Cannulated Headed Screw, Long Thread
319-4551	4.5 x 50 mm Cannulated Headed Screw, Long Thread
319-4556	4.5 x 55 mm Cannulated Headed Screw, Long Thread
319-4561	4.5 x 60 mm Cannulated Headed Screw, Long Thread
319-4566	4.5 x 65 mm Cannulated Headed Screw, Long Thread
319-4571	4.5 x 70 mm Cannulated Headed Screw, Long Thread



Washer

316-0325 4.5 mm Screw Washer