

Item Catalogue

NUPCO CODE: 4232150034400 | SN: 994

NUPCO ITEM DESCRIPTION

WASHER, FOR CANNULATED TITANIUM SCREW FULL THREADED 8MM, ASSORTED SIZES

VENDOR PRODUCT DESCRIPTION

Acumed Cannulated Screw Washer, 13.0 mm OD x 6.7 mm ID

SKU CODES INCLUDED FOR THIS NUPCO CODE

7003-13067

Ordering Information [continued]

Tray Components — 3.0 mm Driver and Drill Module

1	Ø3.0 mm Screw & Instrument Module, ExtremiFix Small	316-1530	2	Ø2.3 mm Cannulated Drill, Quick Release	316-0532
3	Ø3.0/4.0 mm Cannulated Countersink, Quick Release	316-0501	4	Ø3.2 mm Proximal Cortex Drill, Quick Release	316-0533
5	Ø2.3 mm Drill/Countersink Combo, Short, Quick Release	316-0537	6	Ø2.3 mm Drill/Countersink Combo, Long, Quick Release	316-0538
7	Ø3.0/4.0 mm T10 Driver, Cannulated, Short, Quick Release	316-0554	8	Ø3.0/4.0 mm T10 Driver, Cannulated, Long, Quick Release	316-0555

Tray Components — 3.0 mm Screw Module

9	Ø3.0 mm Screw & Instrument Module, ExtremiFix Small	316-1530	10	Cannulated Depth Gauge, Double sided 4"/6"	316-0036
11	Ø.045 x 6" K-wire	316-0004	12	Ø.045 x 6" Partially Threaded K-wire	316-0006
13	Ø.045 x 6" Double Trocar K-wire	316-0122	14	Ø.045 x 4" K-wire	316-0003
15	Ø.045 x 4" Double Trocar K-wire	316-0123	16	Ø3.0 mm Washer	316-0225

Tray Components — 3.0 mm Screw Module

17	3.0 mm Headed Cannulated Screws		18	3.0 mm Headless Cannulated Screws	
	3.0 x 10 mm Cannulated Headed Screw	318-3010		3.0 x 10 mm Cannulated Headless Screw	315-3010
	3.0 x 12 mm Cannulated Headed Screw	318-3012		3.0 x 12 mm Cannulated Headless Screw	315-3012
	3.0 x 14 mm Cannulated Headed Screw	318-3014		3.0 x 14 mm Cannulated Headless Screw	315-3014
	3.0 x 16 mm Cannulated Headed Screw	318-3016		3.0 x 16 mm Cannulated Headless Screw	315-3016
	3.0 x 18 mm Cannulated Headed Screw	318-3018		3.0 x 18 mm Cannulated Headless Screw	315-3018
	3.0 x 20 mm Cannulated Headed Screw	318-3020		3.0 x 20 mm Cannulated Headless Screw	315-3020
	3.0 x 22 mm Cannulated Headed Screw	318-3022		3.0 x 22 mm Cannulated Headless Screw	315-3022
	3.0 x 24 mm Cannulated Headed Screw	318-3024		3.0 x 24 mm Cannulated Headless Screw	315-3024
	3.0 x 26 mm Cannulated Headed Screw	318-3026		3.0 x 26 mm Cannulated Headless Screw	315-3026
	3.0 x 28 mm Cannulated Headed Screw	318-3028		3.0 x 28 mm Cannulated Headless Screw	315-3028
	3.0 x 30 mm Cannulated Headed Screw	318-3030		3.0 x 30 mm Cannulated Headless Screw	315-3030
	3.0 x 32 mm Cannulated Headed Screw	318-3032		3.0 x 32 mm Cannulated Headless Screw	315-3032
	3.0 x 34 mm Cannulated Headed Screw	318-3034		3.0 x 34 mm Cannulated Headless Screw	315-3034
	3.0 x 36 mm Cannulated Headed Screw	318-3036		3.0 x 36 mm Cannulated Headless Screw	315-3036
	3.0 x 38 mm Cannulated Headed Screw	318-3038		3.0 x 38 mm Cannulated Headless Screw	315-3038
	3.0 x 40 mm Cannulated Headed Screw	318-3040		3.0 x 40 mm Cannulated Headless Screw	315-3040

System Features

Wide Range of Screw Lengths

Provided to address a wide variety of fracture patterns.

Cancellous thread form
Designed to maximize purchase in cancellous bone

Low-profile head
Designed to reduce possibility of soft tissue irritation in comparison to standard screw heads

Fully threaded screws
Intended to be used to stabilize fractures with little to no compression across the fracture

Reverse cutting flutes
Designed to assist in removal of partially threaded screws
Note: Reverse cutting flutes only available on select screws

Partially threaded screws
May be used to lag one bone fragment to another, where the far bone fragment is captured by the threads of the screw and pulled towards the near cortex fragment on the head side of the screw

Short Thread 16 mm



(3005-XXXXX)
30–150 mm

Long Thread 32 mm



(3006-XXXXX)
45–150 mm

Full Thread



(3007-XXXXX)
30–150 mm

Cannulated Screw Washer



(7003-13067)
13.0 mm OD x 6.7 mm ID

6.5 mm/7.3 mm Cannulated Screws	
Driver Size	4.0 mm Cannulated Driver (80-1874)
Drill Size	5.0 mm Cannulated Drill (80-1871)
Guide Wire Size	2.8 mm (.110") x 300 mm Threaded (80-1878) 2.8 mm (.110") x 300 mm Fluted (80-2535) 2.8 mm (.110") x 450 mm Threaded (80-2533)
Washer Size	13.0 mm Outer Diameter (OD) x 6.7 mm Inner Diameter (ID) (7003-13067)

Ordering Information [continued]

7.3 mm Cannulated Screws

7.3 mm Cannulated Screw—Full Thread

7.3 mm x 30 mm Cannulated Screw Full Thread	3007-73030	7.3 mm x 95 mm Cannulated Screw Full Thread	3007-73095
7.3 mm x 35 mm Cannulated Screw Full Thread	3007-73035	7.3 mm x 100 mm Cannulated Screw Full Thread	3007-73100
7.3 mm x 40 mm Cannulated Screw Full Thread	3007-73040	7.3 mm x 105 mm Cannulated Screw Full Thread	3007-73105
7.3 mm x 45 mm Cannulated Screw Full Thread	3007-73045	7.3 mm x 110 mm Cannulated Screw Full Thread	3007-73110
7.3 mm x 50 mm Cannulated Screw Full Thread	3007-73050	7.3 mm x 115 mm Cannulated Screw Full Thread	3007-73115
7.3 mm x 55 mm Cannulated Screw Full Thread	3007-73055	7.3 mm x 120 mm Cannulated Screw Full Thread	3007-73120
7.3 mm x 60 mm Cannulated Screw Full Thread	3007-73060	7.3 mm x 125 mm Cannulated Screw Full Thread	3007-73125
7.3 mm x 65 mm Cannulated Screw Full Thread	3007-73065	7.3 mm x 130 mm Cannulated Screw Full Thread	3007-73130
7.3 mm x 70 mm Cannulated Screw Full Thread	3007-73070	7.3 mm x 135 mm Cannulated Screw Full Thread	3007-73135
7.3 mm x 75 mm Cannulated Screw Full Thread	3007-73075	7.3 mm x 140 mm Cannulated Screw Full Thread	3007-73140
7.3 mm x 80 mm Cannulated Screw Full Thread	3007-73080	7.3 mm x 145 mm Cannulated Screw Full Thread	3007-73145
7.3 mm x 85 mm Cannulated Screw Full Thread	3007-73085	7.3 mm x 150 mm Cannulated Screw Full Thread	3007-73150
7.3 mm x 90 mm Cannulated Screw Full Thread	3007-73090	2 7.3 mm Cannulated Screw Caddy	80-1827

Optional

Implants

Cannulated Screw Washer 13.0 mm OD x 6.7 mm ID	7003-13067
---	------------

To learn more about the full line of Acumed innovative surgical solutions, please contact your local Acumed sales representative, call 888.627.9957, or visit www.acumed.net.

Acumed® 6.5 mm/7.3 mm Cannulated Screw System Surgical Technique

Notes: